

The Odyssey K3 utilises the patented curved hydraulic ankle as well as a higher frequency carbon fibre foot base for increased dynamic response. The angular positioning and robust ankle housing are specifically designed to support moderate activity users who change terrain and speed regularly.


The combination of smooth hydraulics and a dynamic foot base increases ground contact, which reduces socket interface pressures and enhances knee stability. The Odyssey K3 performs exceptionally in a wide range of activities, including city walking and multi-terrain hiking.

Features and Benefits

- Low-profile, curved hydraulic ankle
- Robust ankle housing combined with a carbon composite keel and angular positioning designed for moderate impact users
- Easily accessible, independently adjustable hydraulic valves for tuning in clinic
- 12° of smooth hydraulic motion (3° dorsiflexion, 9° plantarflexion)



One pivot angle



Customisable Stride Control®

Cosmetics



Solid toe foot shell



Ordering Information

Trial Period - This foot has a 30 day trial period.

Impact Level Descriptions

Low: Daily activities include mostly level ground walking, moving around the home and the community.

Moderate: Daily activities include up to unlimited walking, climbing stairs and occasional moderate lifting (this does not include running).

Ordering Example: NODK3-LCEN-22-G5

Part ID	Side	Shell Colour	Mounting	Size	Firmness Category
NODK3	L		EN		G
NODK3	R		EN		G

Caucasian	C
Tan	T
Brown	B

21-30cm

1-5
See Chart Below

Firmness Category	0-63	64-81	82-100	101-125
Weight (kg)				
Size (cm)	21-30			
Low Impact	1	2	3	4
Moderate Impact	2	3	4	5

Spare Parts Ordering Information

Foot Shell	Size (cm)
NHZ-S ■ ● ▲	21-30



- = "L" or "R" for Left or Right
- = Colour (C = Caucasian, T = Tan, B = Brown)
- ▲ = Foot size in cm (21-30)

Shelltread	Size (cm)
NHZ-T ■ N-▲	21-30



Neutral

CPI Spectra Sock	Size (cm)
NCPI-SS-SM	Small (19-25cm)
NCPI-SS-LG	Large (26-31cm)
NCPI-SSK-SM	Small 6 pack (19-25cm)
NCPI-SSK-LG	Large 6 pack (26-31cm)



Product Specification

Mounting	Weight Limit	Sizes	Weight of Unit
Endo (IP)	125kg	21-30cm	750g Size 26 inc. foot shell
Impact Level	Build Height	Warranty	Foot Shell
L M H	8.6-9.1cm	3 years Foot shell - 6 months	C T B Caucasian, Tan or Brown Standard width

Technical Information

