

The Soleus foot integrates multiple composite springs through a tough, flexible plantar ligament. This unique design works consistently across a variety of activity levels. Multiple springs work together to maximise range of motion and balance shock absorption with very efficient energy return and superior compliance.

CES CPI F06: Use this code to read the Soleus clinical evaluation summary on the Steeper website.



***Waterproof note:** Following exposure to chlorinated water, rinse immediately with fresh water and dry.

Features and Benefits

- Efficient energy return
- Waterproof design
- Integrated Spring Technology (IST)
- Polycentric ankle motion
- Vertical shock absorption
- Multi-axial compliance

Cosmetics



CAP Solid toe foot shell

Note: Please see the following page for Soleus spare parts ordering information.



Ordering Information

Trial Period - This foot has a 30 day trial period.

Impact Level Descriptions

Moderate: Daily activities include up to unlimited walking, climbing stairs and occasional moderate lifting (this does not include running).

High: Daily activities include fast walking, jogging, running, lifting heavy objects and/or recreational sports.

Note: Please see the following page for Soleus spare parts ordering information.

Ordering Example: NSO-LCM-27W-G12

Part ID	Side	Shell Colour	Housing Colour	Size	Width**	Firmness Category
NSO	L					G
NSO	R					G

Includes foot shell, CPI Spectra Sock and fasteners to mount the 4-hole adapter of your choice.


Caucasian	C	Midnight Black	M	21-30cm	Narrow	N	11-76
Jet Black	J				Wide**	W	
Brown	B				24-30cm only		
Tan	T						

Weight (kg)	Sizes 21-24cm		Sizes 25-26cm		Sizes 27-30cm	
	Moderate Impact	High Impact	Moderate Impact	High Impact	Moderate Impact	High Impact
0-45	11	12	12	12	11	12
46-54	12	33	12	32	11	12
55-63	33	34	32	33	12	32
64-72	34	54	33	54	32	33
73-81	54	55	54	55	33	34
82-91	55	55	55	75	34	54
92-100	55	-	75	76	54	55
101-113	-	-	76	76	55	55
114-125	-	-	-	-	55	55

Product Specification


Sizes	Weight Limit	Build Height	Weight of Unit
21-24cm	100kg	16.3cm	667g Size 26 inc. foot shell
25-26cm	113kg	18cm	
27-30cm	125kg	19.3cm	
Impact Level	Warranty	Foot Shell	
MH	3 years Foot shell - 6 months	C T B J Caucasian, Tan, Brown or Jet Black Narrow or Wide width	

Technical Information



Spare Parts Ordering Information

Foot Shell	Size (cm)
NV-S ■●-▲N	21-30
NV-S ■●-▲W	24-30




- = "L" or "R" for Left or Right
- = Colour (C = Caucasian, T = Tan, B = Brown, J = Jet Black)
- ▲ = Foot size in cm (21-30)
- N = Narrow, W = Wide

Shelltread	Size (cm)
NV-T ■●-▲N	21-30
NV-T ■●-▲W	24-30



- = "L" or "R" for Left or Right
- = Colour (N = Neutral, J = Jet Black)
- ▲ = Foot size in cm (21-30)
- N = Narrow, W = Wide




CAP	Size (cm)
NV-C ■●-2124	21-24
NV-C ■●-2526	25-26
NV-C ■●-2730	27-30



- = "L" or "R" for Left or Right
- = Colour (C = Caucasian, T = Tan, B = Brown, J = Jet Black)

CPI Spectra Sock	Size (cm)
NCPI-SS-SM	Small (19-25cm)
NCPI-SS-LG	Large (26-31cm)
NCPI-SSK-SM	Small 6 pack (19-25cm)
NCPI-SSK-LG	Large 6 pack (26-31cm)



Adapters	Description	Weight Limit
1 N4HPA-T	4-Hole Male Pyramid Adapter, Standard, Titanium	136kg
2 N4HPAR-T	4-Hole Male Pyramid Adapter, Rotatable, Titanium	136kg
3 NTI-460TRM	4-Hole Clamping Base With Pyramid	166kg
4 NTI-400B	Titanium 4 Hole Pyramid Adapter	166kg

